

# EV CHARGING \*

**MASTERPLUG SOCKETED** & TETHERED SMART **EV CHARGERS** 













- Connect via Wi-Fi or LAN
- Fully compliant with The Electric Vehicles (Smart Charge Points) Regulations 2021, including Schedule 1
- Full Smart! charging via the Monta App
- Dynamic charging up to 7.4KW (32A)
- No earth rod required, integrated open PEN conductor protection
- Safe with a Integrated Type A RCD with 6mA DC detection
- OCCP 1.6J connectivity
- Type 2 Socket with Auto-Lock or 5M tethered options

## **CHARGE-POINT APP**

Included at no additional cost, Monta lets you tailor your EV Smart Charging needs. Have full control over your charge-point; deciding who can use it, when and at what cost



Smart charging



Self-healing



**Æ** Solar charge ready



24/7 app support



Share & monetise your charger



#### **RANGE FEATURES**

CODES: S7 SOCKET

EVCM3SS7B

**T7 5M TETHERED** 

EVCM3ST7B

**SOCKET / PLUG:** TYPE 2 CONNECTOR

**CHARGE CURRENT: CONFIGURABLE 6-32A** 

INPUT VOLTAGE: 220-240V 50-60HZ SINGLE PHASE

COLOUR: BLACK - RAL9005

IP / IK RATING: IP55 / IK08

**MATERIAL:** UV RESISTANT POLYCARBONATE

**WALL FIXING:** 4 POINT FIXING WITH HORIZONTAL

AND VERTICAL ADJUSTMENT. SUPPLIED WITH FIXING HOLE

TEMPLATE. FIXING CENTRES - 110MM

X 145MM

**CABLE MANAGEMENT:** INTEGRATED CABLE STORAGE

-25°C TO + 50°C, INTEGRATED **OPERATING TEMP:** 

THERMAL PROTECTION


INCLUDED LOAD MANAGEMENT CLAMP,


**ACCESSORIES:** 1X25MM COMPRESSION GLAND,

1X25MM BLIND GROMMET. ANTI-TAMPER DRIVER BIT, POWER CONNECTORS AND 5X BASE FIXING

WASHERS

#### **DIMENSIONS:**





#### **NETWORK AND CONNECTIVITY**

WI-FI: 2.4GHZ 802.11 B/G/N

WI-FI SECURITY: WPA/WPA2/WPA2-ENTERPRISE

RJ45. SUPPORTS DHCP AND **ETHERNET:** 

MANUAL STATIC IP ADDRESS

CONNECTION

PROTOCOL:

EASY SET UP VIA BLUETOOTH **BLUETOOTH:** 

OCPP 1.6J

INSTALLER APP, 4.2BR/EDR AND BLE

APP: POWERED BY MONTA USER APP

### **ELECTRICAL AND SAFETY**

**PEN PROTECTION:** YES, INTEGRATED EARTH

DISCONNECTION

**EARTH ROD:** NOT REQUIRED, SUPPORTS TT, TN C-S,

PME

**RCD PROTECTION:** YES, INTEGRATED 6MA DC AND 30MA

AC TYPE A

CLASS 1, WITH CLASS 2 HOUSING FOR **ELECTRICAL CLASS:** 

PEN FAULT PROTECTION

SUPPLIED WITH LOAD MANAGEMENT **LOAD MANAGEMENT:** 

CLAMP, SUPPORTS UPTO 120A

**CIRCUITS** 

**METER ACCURACY:** 2% CLASS C EQUIVALENT INTERNAL

METER, SUPPORTS EXTERNAL RS485

MODBUS METER

40A MCB OR 30MA TYPE A RCBO **CONSUMER UNIT** 

**REQUIREMENTS:** (DEPENDENT ON CABLE TYPE AND/

OR ROUTE)

**TERMINALS:** COMBI SCREW FIRST FIX POWER

PLUG

**INDICATOR:** RBG LED AND BUZZER

**BLUE - STANDBY** 

FLASHING BLUE - PREPARING

GREEN - CHARGING

FLASHING GREEN - CHARGE FINISHED

YELLOW - NO NETWORK

RED - ERROR

**WARRANTY:** 3 YEAR STANDARD WARRANTY

STANDARDS AND **APPROVALS:** 

IEC61851-1, IEC61439-7, IEC 62955, IC 61851-21-2, BS EN62196, EN301 511, EN 301 908-1/2/13, EN 301 489-3, EN 300 330, EMC COMPLIANT, THE ELECTRIC VEHICLES (SMART CHARGE POINTS) **REGULATIONS 2021 INCLUDING** 

SCHEDULE 1